



SPARE wózki widłowe
 Al. Jerozolimskie 261, 05-816 Michałowice k/Warszawy
 tel / fax: 0- 22 723 92 90
 e-mail : info@spare.pl
www.spare.pl

Zalecane ciśnienie w oponach pneumatycznych **Ad-trak** do wózków widłowych.

Rozmiar opony	Liczba PR (przekładek)	Zalecane ciśnienie w oponie [bar]
4.00 - 8	6	8.00
	6	8.00
	8	9.00
	8	9.00
	10	10.00
5.00 - 8	6	6.50
	8	8.25
	10	10.00
16 x 6 - 8 (150/75-8)	14	8.50
	16	9.00
18 x 7 - 8 (180/70-8)	8	7.00
	10	8.00
	14	9.00
	16	10.00
	18	10.50
6.00 - 9	10	8.50
	10	8.50
	12	10.00
21 x 8 - 9 (200/75 - 9)	14	9.00
	16	10.00
6.50 - 10	10	7.75
	10	7.75
	12	9.00
	14	10.00
7.50 - 10	12	8.00
	16	10.00
23 x 9 - 10 (225/75-10)	14	7.00
	16	8.00
	18	9.00
	20	10.00



SPARE wózki widłowe
 Al. Jerozolimskie 261, 05-816 Michałowice k/Warszawy
 tel / fax: 0- 22 723 92 90
 e-mail : info@spare.pl
www.spare.pl

7.00 - 12	12	8.50
	14	9.00
	16	10.00
23 x 10 - 12 (250/55-12)	14	8.25
	16	9,75
27 x 10 - 12 (250/75-12)	14	7.00
	16	8.00
	20	9.00
	24	10.00
23 x 5	6	5.25
	8	6.50
	10	7.75
7.00 -15	14	9.00
7.50 - 15	10	7.00
	12	8.00
	14	9.25
	16	10.00
8.25 - 15	12	7.00
	14	8.00
	16	9.25
	16	9.25
28x9-15 (8.15-15) (225/75-15)	12	8.25
	14	9.00
	16	9.75
250 - 15 (250/70-15)	16	8.25
	20	10.50
300 -15 (315/70-15)	18	8.00
	20	9.50
28x12.5-15 (315/50-15)	24	10.00
10.00 - 20	16	9.00
12.00 - 20	20	10.00